

MH-380 (parallel 2-needle) MH-382 (tandem 2-needle) High-speed, Flat-bed, 2-needle Double Chainstitch Machine



MH-380 · MH-382

Various attachments allow the machine to adapt to many different processes.

Accurate stitching performance and durable finished seams are particularly necessary in the chainstitching process. JUKI ensures high-quality sewing with a higher degree of consistency with its unique looper mechanism and consistent condensation stitching mechanism. Furthermore, highly efficient operation is achieved by using a chain-off thread cutting device.



The machine ensures outstanding reliability and durability.

It comes with JUKI's unique inclined crank type looper mechanism. This gives the machine outstanding durability. You can use the sewing machine for a long time without ever worrying about looper failure.

The machine is capable of performing consistent condensation stitching, ensuring finished seams of higher quality.

You can easily set the machine to perform condensation stitching by operating the lever. Condensation stitches that prevent the thread from fraying can be consistently sewn.

Stitch length can be adjusted with ease.

The machine incorporates a stitch dial for adjusting the stitch length. For lockstitch machines, which are the most popular type of sewing machines, the stitch length is also adjusted using a stitch dial. This means you can adjust the stitch length as desired without difficulty.

DEVICES AND ATTACHMENTS

working wear.



APPLICATIONS

		-
Model	Application	
MH-380 (parallel 2-needle)	 Sewing sides of slacks Hemming or welting garment parts Attaching lining tape 	
MH-382 (tandem 2-needle)		Rear moving Right fix Loft pacello guar
TABLE OF EXCH	ANGING GAUGE SETS	gkhans
Description Throat pla	te Needle clamp Presser foot asm. Feed dog	Rear moving Right fix Left needle guard

Applicable machines: MH-380, MH-382

Applications: Cut a chaining thread bridging two

workpieces continuously sewn by chainstitch in the way

that a knife blade of the cutter is dropped. Best suited

for continuous sewing on pocket openings of jeans or

Class of work: Jeans, Working wear

TABLE OF EXCHANGING GAUGE SETS

MH-380					210-		
Description	Throat plate	Needle clamp	Presser foot asm. (with finger	Feed dog	Rear moving needle guard	Right fix needle guard	Left needle guard
Gauge components				ED.			J
3.2mm (1/8")	B1103-380-B00	B1406-019-BA0	B1509-038-BB0	B1613-380-B00			
4.0mm (5/32")	¥1103-380-C00	B1406-019-CA0	B1509-038-CB0	B1013-380-B00	B2311-380-B00		
4.8mm (3/16")	B1103-380-D00	B1406-019-DA0	B1509-038-DB0	B1613-380-D00			
5.6mm (7/32")	B1103-380-E00	B1406-019-EA0	B1509-038-EB0	B1613-380-F00	B2311-380-E00	B2315-380-000	B2312-380-000
6.4mm (1/4")	B1103-380-F00	B1406-019-FA0	B1509-038-FB0	B1013-360-F00	B2311-360-E00	B2313-380-000	B2312-380-000
7.9mm (5/16")	B1103-380-H00	B1406-038-HA0	B1509-038-HB0	B1613-380-H00	D2211 200 LIOO		
9.5mm (3/8")	B1103-380-K00	B1406-038-KA0	B1509-038-KB0	B1613-380-K00 B2311-380-H00			
12.7mm (1/2")	B1103-380-L00	B1406-038-LA0	B1509-038-LBB	B1613-380-L00	B2311-380-L00		
MH-382							

_	B1103-382-000	B1406-019-BA0	B1524-382-0B0	B1613-382-000	B2311-382-000	B2312-382-000

MH-380

MI1-560						
Description	Right looper Left looper		Bed slide asm.	Bed slide asm.		
Gauge components			$\overline{\mathbf{S}}$	\sim		
3.2mm (1/8")						
4.0mm (5/32")		B2031-380-000				
4.8mm (3/16")			B1104-380-AA0	B1108-380-BA0		
5.6mm (7/32")	B2030-380-000					
6.4mm (1/4")	B2030-380-000					
7.9mm (5/16")						
9.5mm (3/8")				B1108-380-HA0		
12.7mm (1/2")			B1104-380-LA0	B1108-380-LA0		
MH-382						
—	B2030-380-000	B2031-380-000	B1104-380-AA0	B1108-380-BA0		

Size code

Guide width mm (in)

Tandem 2-needle

4.0 (5/32)

4.8 (3/16)

6.4 (1/4)

7.9 (5/16)

Part No.

40042785

40042787

40042788

40042790

40042791

3.2mm (1/8") = B
4.0mm (5/32") = C
4.8mm (3/16") = D
5.6mm (7/32") = E
6.4mm (1/4") = F
7.9mm (5/16") = H
9.5mm (3/8") = K
12.7mm (1/2") = L

SPECIFICATIONS

Madalaama	MH-380	MH-382			
Model name	Parallel 2-needle	Tandem 2-needle			
Max. sewing speed	6,000sti/min *				
Max. stitch length	4n	ım			
Lift of the presser foot	By hand: 5.5mm,	By knee: 10mm			
Needle bar stroke	30r	nm			
Needle (at the time of delivery)	TV×7 (#14) #9~#21				
Thread take-up	Needle bar thread take-up				
Stitch length adjustment	By stitch dial (lockstitch)				
Condensation stitches	By lever for condensation stitching				
Looper system	Rocking type looper				
Looper stroke	22.6mm				
Elliptical motion	2.4~3.7mm				
Lubrication	Automatic				
Lubricating oil	JUKI New Defrix Oil No.1 (equivalent to ISO VG7)				
Needle cooler	Optional				
* "sti/min" stands for "Stiches per Minute"					

MH382U

WHEN YOU PLACE ORDERS

MH380 U

Please note when placing orders, that the model name should be written as follows:

		L							
	Code	В	С	D	E	F	н	К	L
Needle	mm	3.2	4.0	4.8	5.6	6.4	7.9	9.5	12.7
gauge	inch	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2



JUKI CORPORATION HEAD OFFICE

tion operates an environmenta conduct the following as the elopment, design, sales, distri ent of products and engineering pri cesses that are safe ronment and green purchasing urement and green purchasing saving (reduction in carbon-dioxide emissions) saving (reduction of papers purchased, etc.) and rocycling of waste ent of logistics efficiency (modal shift and improvemi packing, etc.) (2) Green pr (3) Energy c (4) Resource (5) Reductio (6) Improve packagin

• To order, please contact your nearest JUKI distributor.



R 2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN PHONE : (81) 42-357-2254 FAX : (81) 42-357-2274 http://www.juki.com

* Specifications and appearance are subject to change without prior notice for improvement.

* Read the instruction manual before putting the machine into service to ensure safety.

 $\boldsymbol{*}$ This catalogue prints with environment-friendly soy ink on recycle paper.