




GT-288CF

可变线量双步进电脑平缝机
Take-up Thread Variable Double Stepping
Motor Computer Lockstitch Sewing Machine




挑线杆专利
厚薄通吃
Thread take-up lever patent
versatile for thick and thin
fabrics both



双步进电机，更安静平稳
Double stepper motor for
quieter and smoother




双圆刀的新切线机构，(短线头、减少线头堆积现象)
New mechanism for double round cutter (short thread tale,
reduced thread piling)




步进电机控制剪线、抬压脚
Stepper motor control cutting
thread, lifting presser foot



电子松线,自动调整面线张力
Electronic thread loose,
automatic adjustment of
surface tension



密封油盘，无油无虑
Closed oil pan design



西装 suit



T恤 T-shirt



牛仔 Denim



羽绒服 Down jacket



衬衫 Shirt

性能参数 TECHNICAL DATA

机型 Machine type	机针 Machine needle	针距 Needle gauge	抬压脚高度 Foot lifter height	厚料 Thick fabrics	中厚料 Medium fabrics	薄料 Thin fabrics	自动剪线 Auto thread trimming	大旋梭 Big hook	小旋梭 Small hook	最高转速(rp.m) Max speed	包装尺寸 Package size	毛重/净重 Gross/net weight
GT-288CF	DBx1	0-7	5.5-13	—	★	★	★	—	★	5000	680x285x635	45/39
GT-288CF-H	DPx5	0-7	5.5-13	★	—	—	★	—	★	4500	680x285x635	45/39




GT-288ZS


针送料步进电脑平缝机
needle feed stepping computer
lockstitch sewing machine

技术特色 PRIMARY CHARACTERISTIC

- 送料顺，防错层，不起皱，不错位
1. Smooth fabric feeding, anti-split-layer, wrinkle-free, no dislocation;
- 采用双独立步进电机马达驱动剪线与电磁铁，更安静，更平稳，
2. Double independent stepper motor drive thread trimming and electromagnet, quieter, more stable,
- 密封油盘，避免油污污染面料；
3. Sealed oil pan to avoid oil contamination of the fabric;



针送料，防错层
Needle feed, anti-split-layer




双步进电机，更安静平稳
Double stepper motor for
quieter and smoother



双圆刀的新切线机构，有效减少对线头的处理工作(短线头、减少线头堆积现象)
Double round knives cutting mechanism, effectively reducing process of
dealing with the thread head (shorter thread head, less thread piling)



普通平缝机 Ordinary sewing machine




GT-288ZS



密封油盘
Sealed oil pan



西装 suit



西裤 Suit pants



衬衫 Shirt



T恤 T-shirt

性能参数 TECHNICAL DATA

机型 Machine type	机针 Machine needle	针距 Needle gauge	抬压脚高度 Foot lifter height	厚料 Thick fabrics	中厚料 Medium fabrics	薄料 Thin fabrics	自动剪线 Auto thread trimming	大旋梭 Big hook	小旋梭 Small hook	最高转速(rp.m) Max speed	包装尺寸 Package size	毛重/净重 Gross/net weight
GT-288ZS	DBx1	0-5	5.5-13	—	★	★	★	—	★	5000	680x285x635	45/39
GT-288ZS-H	DPx5	0-5	5.5-13	★	—	—	★	—	★	4500	680x285x635	45/39