



GT-845/GT-875

智能直驱拐角双针平缝机
Smart direct drive cornering double
needle lockstitch sewing machine



GT-842/GT-872

智能直驱双针平缝机
Smart direct drive double needle
lockstitch sewing machine



本产品型式为平板式机体，采用直针刺布、连杆或滑杆挑线、双立式旋梭勾线、机针下复合送料。采用计算机控制系统、伺服电机直接驱动、倒回缝线迹重合度高，大功率电机使机针贯穿力更强。更能实现厚料及台阶部分的缝纫。

This product type is flat-bed body, using straight needle to sew fabrics, connecting rod or slide rod for thread take-up, double vertical rotary shuttle hook for thread and bottom compound needle feed. Using computer control system, servo motor direct drive, reverse sewing stitches are highly matched, high power motor makes machine needle force more stronger. It can realize the sewing of thick material and overlaps.

性能参数 TECHNICAL DATA


机型 Machine type	机针 Machine needle	抬压脚高度 Foot lifter height	针杆行程 needle bar stroke	针间距 Needles distance	针位组 Needle gauges	最高转速(rp.m) Max speed	包装尺寸 Package size	毛重/净重 Gross/net weight
GT-842-3	DPx5 (11#-16#)	7-13	33.5	4		3500	675x310x660	48/43
GT-842-5	DPx5 (16#)-22#)	7-13	34	5	1/8" (3.2mm)	3000	675x310x660	48/43
GT-872	DPx5 (16#)-22#)	7-13	34	7	5/32"(4.0mm) 7/32"(5.6mm)	3000	675x310x660	48/43
GT-845-3	DPx5 (11#-16#)	7-13	33.5	4	1/4" (6.4mm)	3500	675x310x660	48/43
GT-845-5	DPx5 (16#)-22#)	7-13	34	5	3/8" (9.6mm)	3000	675x310x660	48/43
GT-875	DPx5 (16#)-22#)	7-13	34	7		3000	675x310x660	48/43



GT-N95130J-R

智能模板机旋转缝带升降系列
Intelligent rotary-head template machine with
laser cutting & lifting function series

适用缝制范围 Suitable sewing range:
X轴向X axis: 1300mm
Y轴向Y axis: 890mm




Y向双丝杆传动



激光切割装置
Laser cutting device



机头可升降



一体铸造机臂

性能参数 TECHNICAL DATA

缝制范围 Sewing range	最高转速(rp.m) Max speed	针距 Needle gauge	机针 Machine needle	压脚行程 Presser foot stroke	抬压脚高度 Foot lifter height	花样储存 Pattern storage	Y送料方式 Y feeding mode	包装尺寸 Package size	量重 Weight
1300x890mm	3500	0. 1-12.7	DPx5 DPx17	15	22	999	双丝杆	1960x1310x1860	920