



GT-333

步进智能电脑同步车
Stepping Intelligent Computer Top & bottom
Feeding Lockstitch Sewing Machine



● 技术特色 PRIMARY CHARACTERISTIC

本机为新一代智能电脑同步机，采用按键屏幕，用指尖简单点击输入，缝纫功能设置即可轻松完成。按键操作设定简单，大量使用简单易懂的插图图标，可进行直观操作。

采用最新的机电一体式结构，操作简便，适用于缝制中厚料皮革服装等面料，采用大旋梭，减少换底线次数，提高工作效率；采用全自动润滑装置，提高机器使用寿命。

This machine is a new generation of intelligent computer top&bottom feed lockstitch sewing machine, using the key screen, simple click to input with fingertips, sewing function setting can be easily completed. Key operation setting is simple, a large number of easy-to-understand illustration ICONS, can be intuitive operation.

Adopt the latest electro-mechanical integrated structure, easy to operate, suitable for sewing medium thick leather clothing and other fabrics, the use of large hook, reduce the number of bottom thread change, improve work efficiency; Automatic lubrication device is adopted to improve the service life of the machine.



步进电机控制针距
步进电机控制自动抬压脚
Stepper motor control
needle distance
Stepper motor control
automatic lift presser foot



智能显示屏，操作便捷
Smart display, easy to
operate



超能USB接口，
方便系统升级
Super USB interface,
easy to upgrade the
system

● 性能参数 TECHNICAL DATA

机型 Machine type	机针 Machine needle	线数 thread number	抬压脚高度 Foot lifter height	针距 Needle gauge	针杆行程 needle bar stroke	大旋梭 Big hook	最高转速(rp.m) Max speed	包装尺寸 Package size	毛重/净重 Gross/net weight
GT-333	DPx17	1	6/13	9	35	★	2800	580x250x530	45/39
GT-333(大针距)	DPx17	1	6/13	12	35	★	2800	580x250x530	45/39



GT-8450

双步进智能拐角双针机
Double stepping motor smart
cornering double needle
sewing machine



● 技术特色 PRIMARY CHARACTERISTIC

本产品型式为平板式机体，采用直针刺布、连杆或滑杆挑线、双立式旋梭勾线、机针下复合送料。采用计算机控制系统、伺服电机直接驱动、步进电机控制针距长度等多轴联动技术、根据转角角度计算、分配针数和针距大小，实现自动转角缝纫、装饰线迹缝纫、停针位、自动剪线、自动拨线、计数缝纫和自动前后加固缝等功能。


This product type is flat-bed body, using straight needle to sew fabrics, connecting rod or slide rod for thread take-up, double vertical rotary shuttle hook for thread and bottom compound needle feed. Using computer control system, servo motor direct drive, stepping motor control stitch length and other multi-axis linkage technology, according to the Angle calculation, distribution for needle numbers and stitches length, realize automatic corner sewing, decorative stitch sewing, needle stop position, automatic thread cutting, automatic thread wiping, count sewing and automatic front and reverse bar-tacking sewing and other functions.



多动能显示屏,操作便捷
Multi-kinetic display, easy
to operate



针杆分离,智能拐角,
直刀剪线,稳定性高;
Needle bar separation,
intelligent corner, straight
knife cutting thread, high stability;



双针机线迹
Two needle
machine stitch

● 性能参数 TECHNICAL DATA

机型 Machine type	机针 Machine needle	抬压脚高度 Foot lifter height	针杆行程 needle bar stroke	针间距 Needles distance	自动剪线 Auto thread trimming	针位组 Needle gauges	最高转速(rp.m) Max speed	包装尺寸 Package size	毛重/净重 Gross/net weight
GT-8420-3	DPx5 (11#-16#)	7-13	33.5	5	★	1/8" (3.2mm)	3500	675x310x660	48/43
GT-8420-5	DPx5 (16#)-22#)	7-13	34	5	★	5/32"(4.0mm)	3000	675x310x660	48/43
GT-8450-3	DPx5 (11#-16#)	7-13	33.5	5	★	7/32"(5.6mm)	3000	675x310x660	48/43
GT-8450-5	DPx5 (16#)-22#)	7-13	34	5	★	1/4" (6.4mm)	3000	675x310x660	48/43
GT-8750	DPx5 (16#)-22#)	7-13	34	7	★	3/8" (9.6mm)	3000	675x310x660	48/43